

FORM PTO-150 (Modified)
(REV 11-98)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES

DESIGNATED/ELECTED OFFICE (DO/EO/US)

CONCERNING A FILING UNDER 35 U.S.C. 371

RCA 88914

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

09/622388

INTERNATIONAL APPLICATION NO.

PCT/US99/03513

INTERNATIONAL FILING DATE

18 February 1999 (18.02.99)

PRIORITY DATE CLAIMED

20 February 1998 (20.02.98)

TITLE OF INVENTION

A MULTIMEDIA SYSTEM FOR ADAPTIVELY FORMING AND PROCESSING EXPANSIVE PROGRAM GUIDES

APPLICANT(S) FOR DO/EO/US

Mehmet Kemal Ozkan, Chia-Yuan Teng and Edwin Arturo Heredia

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c) (2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ A copy of the International Search Report (PCT/ISA/210), attached to item 13
8. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
9. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
10. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).
11. ☒ A copy of the International Preliminary Examination Report (PCT/IPEA/409).
12. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).

Items 13 to 20 below concern document(s) or information included:

13. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98 with references attached
14. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
15. ☒ A **FIRST** preliminary amendment.
16. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
17. ☐ A substitute specification.
18. ☐ A change of power of attorney and/or address letter.
19. ☒ Certificate of Mailing by Express Mail

20. PCT/IB/306-Notification of the Recording of a Change

CERTIFICATE OF MAILING UNDER 37 CFR 1.10

EL694405754US

16 August 2000

"Express Mail" mailing no.

Date of Deposit

I hereby certify that this application is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Davida Fornarotto

Typed or printed name of person
mailing application

Davida Fornarotto
Signature of person mailing
application

523 Rec'd PCT/PTO 16 AUG 2000

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

09/622388

INTERNATIONAL APPLICATION NO.

PCT/US99/03513

ATTORNEY'S DOCKET NUMBER

RCA 88914

21. The following fees are submitted:

BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)):

- ☐ Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$970.00
- ☒ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO \$840.00
- ☐ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$690.00
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$670.00
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) \$96.00

ENTER APPROPRIATE BASIC FEE AMOUNT =

840.00

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	32 - 20 =	12	x \$18.00	216.00	
Independent claims	6 - 3 =	3	x \$78.00	234.00	

Multiple Dependent Claims (check if applicable). ☐**TOTAL OF ABOVE CALCULATIONS = 1290.00**

Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28) (check if applicable). ☐

SUBTOTAL = 1290.00

Processing fee of \$130.00 for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).

TOTAL NATIONAL FEE = 1290.00

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). ☐

TOTAL FEES ENCLOSED = 1290.00

Amount to be refunded	\$
charged	\$1290.00

☐ A check in the amount of _____ to cover the above fees is enclosed.

☒ Please charge my Deposit Account No. 07-0832 in the amount of \$1290.00 to cover the above fees. A duplicate copy of this sheet is enclosed.

☒ The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. 07-0832. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Mr. Joseph S. Tripoli
THOMSON multimedia Licensing Inc.
Patent Department
PO Box 5312
Princeton, New Jersey 08540

SIGNATURE

Ronald H. Kurdyla

NAME

26,932

REGISTRATION NUMBER

16 August 2000

DATE

RECEIVED

AUG 17 2000

Page 2 of 2

533 Rec'd PCT/PTO 16 AUG 2000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Mehmet Kemal Ozkan, Chia-Yuan Teng and
Edwin Arturo Heredia

Filed : Herewith

For : A MULTIMEDIA SYSTEM FOR ADAPTIVELY
FORMING AND PROCESSING EXPANSIVE PROGRAM
GUIDES

PRELIMINARY AMENDMENT

Hon. Commissioner of Patents and Trademarks
Washington, D.C. 20231

Sir:

In the US national phase application of PCT/US99/03513 filed
herewith, please enter the following amendments.

IN THE ABSTRACT:


Please add the attached Abstract.

REMARKS

To meet the requirements of the United States, the Abstract (as
originally filed in the PCT application) is added.

No fee is believed to have been incurred by virtue of this
amendment. However if a fee is incurred on the basis of this amendment, please
charge such fee against deposit account 07-0832

Respectfully submitted,
Mehmet Kemal Ozkan
Chia-Yuan Teng
Edwin Arturo Heredia


Ronald H. Kardyla, Attorney
Registration No. 26,932
609/734-9701

THOMSON multimedia Licensing Inc.
PO Box 5312
Princeton, NJ 08543-5312

16 August 2000

5 A Multimedia System for Adaptively Forming and
 Processing Expansive Program Guides.

Field of the Invention

10 This invention is related to the field of digital signal processing, and more particularly to program guides for channels and programs.

Background of the Invention

15 The formation and processing of large program guides conveying information concerning potentially thousands of broadcast program channels covering a wide geographic area poses a number of problems. The geographic area covered may
20 encompass the whole of the USA or whole continents, for example, and large quantities of information may have to be acquired, collated, encoded and broadcast in a format that facilitates subsequent decoding of the broadcast material. The bandwidth required to process such large quantities of information expands
25 in proportion to the quantity of information being processed. Therefore, there is a need to structure program guide data in order to optimize the use of the available bandwidth.

 The degree to which the program guide data structure may be optimized is constrained by the cost of a decoder unit for
30 receiving the structured data. In fact there is a compromise to be made between transmission bandwidth and decoder complexity. At one extreme of the compromise, all duplicative and redundant data elements in the program guide information are eliminated in order to minimize the required transmission and processing
35 bandwidth. As a result, each decoder needs to receive, buffer, parse and collate information from an entire program guide datastream, thereby necessitating a complex and costly decoder.

 At the other extreme of the compromise, the program guide information is partitioned into individual sub-sets tailored
40 to the requirements of a particular User or group of Users. This

5 means that each decoder needs to receive, buffer, parse and collate targeted information containing minimal redundancy which facilitates employing a simpler, more economical decoder requiring less processing power. However, such partitioning requires a larger transmission bandwidth to accommodate the
10 increased information redundancy resulting from the need to incorporate duplicate program guide information items in multiple different program guide sub-sets corresponding to different partitions. The problems involved in processing large quantities of program guide information and in achieving a desirable
15 compromise between transmission bandwidth and decoder complexity are addressed by a system according to the present invention. Derivative problems involved in structuring and partitioning program guide data to facilitate both decoding and selectable program guide generation by a decoder are also
20 addressed by a system according to the invention.

Summary of the Invention

A decoder acquires data for collating program guide
25 information including objects by both area (e.g. a geographic, broadcast, or network market area), and by scheduled time of broadcast. The decoder collates the program guide information using the collation data which comprises channel and program map information for associating the program guide information
30 with particular areas and broadcast times. The decoder collates the program guide information to provide a program guide selected from at least two available program guides associated with different areas in response to a User selection input. The collated program guide information is processed for display.

35

Brief Description of the Drawings

In the drawing:

5 Figure 1 shows a very large program guide (VLPG) hierarchical file/table format for use in conveying program specific information, according to the invention.

Figure 2 shows a Master Guide Table (MGT) format for
10 use in conveying program specific information, according to the invention.

Figure 3 shows a Channel Information Table (CIT) format for use in conveying program specific information
15 incorporating area based partitioning, according to the invention.

Figure 4 shows a multimedia object data structure format incorporating area and time based partitioning, according
to the invention.

20 Figures 5, 6 and 7 show examples of data structures for channel, event and control object basic information files, according to the invention.

25 Figure 8 shows a data structure for an MPEG compatible carouselId (as used in the tables of Figures 5, 6 and 7) including identifier fields allowing area and time based partitioning.

30 Figure 9 shows a Master Database Table data structure format incorporating hierarchical based version identifiers and cell partition identifiers supporting dynamic program guide re-partitioning, according to the invention.

35 Figure 10 shows an exemplary data structure for a cell type indicator (as used in the table of Figure 9) incorporating area, time and complexity based identifier fields, according to the invention.

5 Figure 11 shows a hierarchical directory format for an object database including channel, event and control sub-directories, according to the invention.

 Figure 12 shows a method for generating program
10 specific information according to the invention.

 Figure 13 is a block diagram of digital video receiving apparatus for demodulating and decoding broadcast signals containing VLPG information, according to the principles of the
15 invention.

Detailed Description of the Drawings

Broadcast programs transmitted in digital format are
20 encoded and broadcast along with ancillary information including program specific information (PSI) used in decoding programs and associated data. Program specific information includes program guide data and information for use in identifying and assembling individual data packets to recover the content of selected program
25 channels. Program specific information and associated program content is advantageously structured to convey large program guides conveying information concerning potentially thousands of broadcast program channels and associated multimedia objects covering a wide geographic area such as whole continents,
30 countries or states, for example. The multimedia objects include audio clips, video clips, animation, still images, Internet data, Email messages, text and other types of data. Multimedia objects are data entities that may be viewed as independent units and are associated with images within individual programs or with
35 program guide components. The multimedia objects are incorporated into composite video images representing a program guide or a video program, for example. The ancillary information data structure supports uni-directional communication applications e.g. passive viewing and bi-directional communication

- 5 applications e.g. interactive type functions and also supports storage applications.

The program specific information and associated program content may be delivered by different service providers via the Internet in broadcast/multicast mode, or via terrestrial,
10 satellite or cable broadcast on a subscription or other pay per view basis. The data structure facilitates acquisition and decoding of multimedia objects encoded in different data formats and which are communicated in different communication protocols from both local and remote sources.

- 15 Hereinafter, data referred to as being MPEG compatible conforms to the MPEG2 (Moving Pictures Expert Group) image encoding standard, termed the "MPEG standard". This standard is comprised of a system encoding section (ISO/IEC 13818-1, 10th June 1994) and a video encoding section (ISO/IEC 13818-2, 20th
20 January 1995).

Data structure elements according to the invention principles may be conveyed in MPEG compatible format (per section 2.4.4 of the MPEG systems standard) or may be conveyed in a format compatible with the *Program and System Information*
25 *Protocol for Terrestrial Broadcast and Cable*, published by the Advanced Television Systems Committee (ATSC), 10 November 1997, hereinafter referred to as the PSIP standard, or other ATSC standards. Further, the data structure elements may be formed in accordance with other MPEG standards such as the MPEG-4 or
30 MPEG-7 standards or with the proprietary or custom requirements of a particular system.

The principles of the invention may be applied to terrestrial, cable, satellite, Internet or computer network broadcast systems in which the coding type or modulation format
35 may be varied. Such systems may include, for example, non-MPEG compatible systems, involving other types of encoded datastreams and other methods of conveying program specific information. Further, although the disclosed system is described as processing broadcast programs, this is exemplary only. The term 'program' is
40 used to represent any form of packetized data such as audio data,

5 telephone messages, computer programs, Internet data or other communications, for example.

Figure 1 shows an overview of a very large program guide (VLPG) hierarchical file/table format for use in a transport stream level data structure conveying program specific
10 information. The structure comprises multiple hierarchically arranged and inter-linked tables. The tables consist of arrays of data and parameters which are used to enumerate and describe collections or sequences of TV channels, TV programs, channel parameters, program parameters, associated multimedia objects
15 and object parameters, etc. The exemplary hierarchical table arrangement of Figure 1 includes a Master Guide Table (MGT) 120, Master Database Table (MDBT) 122, Content and Classification Table (CCT) 114, System Time Table (STT) 116 and Rating Region Table (RRT) 118. The Figure 1 hierarchy also shows Terrestrial,
20 Cable and Satellite Channel Information Tables (TCIT item 112, CCIT item 110, and SCIT item 108 respectively) in which channel information is collated by network provider e.g. CBS, NBC, HBO, Comcast etc. Additional tables include Schedule Information Tables (SIT 106, SIT 104 and SIT 102) in which programs or
25 services are collated by source.

A MGT contains information for use in acquiring program specific information conveyed in other tables. A channel information table - CIT (e.g. TCIT, CCIT, OR SCIT) contains information for tuning and navigation to receive a User selected
30 program channel. A SIT contains descriptive lists of programs (events) receivable on the channels listed in the CIT. Either a CIT, SIT or other table may be used to convey information enabling a user to select and tune to a particular program. A CIT is typically used to convey parameters for acquiring audiovisual program
35 content data that remains constant over several events (TV programs). An SIT is typically used to convey parameters of audiovisual program content data that remain constant for an event (individual TV program). Additional program specific information describing and supplementing items within the

5 hierarchical tables is conveyed within descriptor information elements.

In order to accommodate data sufficient for a wide area program guide, individual tables in the hierarchy of Figure 1 are advantageously partitionable by both area (e.g. a geographic, 10 broadcast, or network market area), and scheduled broadcast time. In addition, the table data may be additionally partitioned in accordance with a third parameter such as the complexity level of data or a multimedia object in order to permit scalability in decoding, for example. This type of program guide partitioning is 15 represented by the 3-dimensional cells depicted in diagram 100. In fact, the VLPG structure of Figure 1 supports virtually any type of partitioning that a guide provider may require. The area and time based partitioning is achieved by including both time and area identifiers in one or more of the tables of Figure 1 and in 20 associated object data. The advantage of including the area and time partition identifiers in the transport level of the communication protocol in this manner is that it reduces the processing burden (e.g. for parsing the data) on a decoder that otherwise occurs if the partitioning is done at a higher level, say 25 the Application layer level. As a result program guide filtering is done at the transport layer and is performed directly by a transport chip contained in a decoder unit. However, it is possible to include the time and area identifiers for both table data and objects at such a higher level if desired.

30 In transmitting and processing a program guide, the bandwidth demand grows with the quantity of channel and program information and number of associated objects that need to be transmitted. For a large program guide, even a simple case may require transmission of thousands of items of information 35 and objects. A simple program guide may have neither images, nor audio, nor video clips, but would still need at least text descriptions for the thousands of programs (events) that it carries. It is possible to send the program guide information without redundancy and without partitions in a single bin or data file. In 40 such a case, and in the absence of transport-level partitions, the

5 text descriptions (for example) will end up in a single data file. This means, for example, that a decoder in San Diego will receive all the material (event text descriptions, images, or any other objects) from all the other cities in the US and will be unable to discard useless material at the transport level. Consequently, in
10 the absence of transport-level partitions, it is necessary for a decoder to filter received program guide information at the application level. This is a processor intensive, time-consuming and burdensome task that requires sophisticated software and significant processing power and raises the cost of a decoder unit.

15 The VLPG data structure of Figure 1 advantageously provides the option of employing area-based partitioning at the transport layer level. Program guide information may be partitioned in an Eastern area, a Central area, a Mountain area, and a Pacific area, for example. Then a decoder in San Diego would
20 no longer need to receive program guide information from the other 3 regions. Therefore, such partitioning significantly reduces the parsing and filtering burden on a decoder and smaller partitions (e.g. on a state by state basis) further reduce the parsing and filtering burden. Another advantage of such
25 partitioning is that the time involved in downloading applicable partitioned program guide information is reduced.

However, partitioning program guide information involves introducing redundant program guide data because such partitioning requires duplication of data items. As an example, if a
30 basketball game is aired in the Pacific and Mountain regions, then two copies of associated text descriptive information need to be transmitted, one copy for each of the partitions targeted at the pacific and mountain regions. It can be seen that, as the number of partitions increases, the quantity of redundant information also
35 increases necessitating larger transmission bandwidth. Consequently, there is a trade-off between bandwidth and the burden of information filtering. A large number of partitions imply fast information filtering but at the cost of increased bandwidth. When there is only one partition, there are no
40 redundancies and therefore bandwidth is minimal but the filtering

- 5 burden is larger since all the program guide information items need to be parsed.

Time and area cells may be mapped into an MPEG-2 compatible data structure by using the MPEG2 PSI and DSM-CC fields. Not all of the tables may need to include area-based
10 identifiers. Program content ratings, for example, are typically applicable everywhere in the US. In the VLPG architecture of Figure 1, significant advantage is obtained by applying area-based partitioning to the Channel Information Table (CIT) and the Master Guide Table. A CIT defines the channel line-up (list of
15 available channels) for a service provider and depends on the geographical area covered by the service provider. The channel line-up for terrestrial broadcast in Indianapolis is different than the channel line-up for a cable provider in Philadelphia, for example. In the system of Figure 1 the MGT also depends on
20 geographical area but this is not necessarily the case.

The capability of performing focused targeting of program guide information to particular audiences is one advantage derived from being able to make fine area-based divisions of channel line-ups at the broadcast market level. In
25 order to accomplish this, different table "instances" are created. A table instance is a version of a table that is targeted to a particular market area and incorporates an area identifier for identifying the applicable market area. Multiple instances of a single table can be concurrently transmitted each carrying different information.
30 Different table instances are recognized using the "table_id_extension" field of the MPEG-2 protocol.

Figures 2 and 3 show a Master Guide Table (MGT) format and Channel Information Table (CIT) format respectively for use in conveying program specific information and
35 incorporating a table_id_extension field for market area identification. In the MGT of Figure 2 and in the CIT of Figure 3, this market area identification field is termed a "network_provider" and is shown in the MGT data structure as item 130, and in the CIT data structure as item 140. The
40 network_provider area identifier field is a 16-bit field used to

10

- 5 uniquely identify a network provider. The meaning of the network provider depends on the transmission medium. Specifically, for terrestrial broadcast, a network provider is a collection of stations within a geographical region, for cable broadcast, a network provider is a local cable service provider and
10 for satellite broadcast, a network provider is a satellite service provider.

- The data structure of Figure 1 advantageously allows different types of program specific and program guide information to be targeted to different areas. This feature permits flexibility in
15 selecting an acceptable compromise between decoder complexity and processing bandwidth involved in broadcasting and receiving the program guide data. As an example, it may be acceptable to partition multimedia objects into coarser areas than channel line-up information. The data structure of Figure 1 gives the guide
20 providers the capability of partitioning different types of data in different gradations of area ranging from coarse areas to fine areas (e.g. areas as large as countries, states, or counties ranging to areas as fine as cities, towns, city blocks or even individual customers).

- 25 Further, program guide information may be collated in a decoder to provide a User a choice between program guides for different areas (e.g. between two neighboring areas or a choice of guides from any of the available areas) or for different periods of broadcast time. As such, a program guide may be selected in a
30 decoder from one or more available program guides associated with different areas, in response to a User selection input via a remote unit or other data entry device. In performing such a selection, a decoder compares a region identification designation (associated with received program guide information) with a pre-
35 stored region identification designation representing the decoder location. Such a region identification designation may comprise, a zip code, a telephone area code, and any other region identification code.

- Figure 4 shows a multimedia object data structure
40 format for conveying objects within a VLPG. The multimedia

5 object data structure supports area and time based partitioning through the use of area and time identifier fields within an MPEG DSM-CC compatible carouselId identifier (item 150 in Figure 4).

Figures 5, 6 and 7 show examples of the data structure of objects comprising channel, event and control objects
10 respectively. Specifically, Figure 5 shows a Channel Basic Information File (channel BIF) binary file, Figure 6 shows an Event Basic Information File (Event BIF) binary file and Figure 7 shows a Control Basic Information File (Control BIF) binary file. In similar fashion to Figure 4, the channel, event and control object data of
15 Figures 5-7 include area and time identifier fields within MPEG DSM-CC compatible carouselId identifiers (items 153, 157 and 159 of Figure 5-7 respectively).

Figure 8 item 152, shows an exemplary carouselId data structure for an MPEG compatible carouselId (as used in the
20 tables of Figures 4, 5, 6 and 7). The carouselId includes a 16 bit directory item identifier for use as a data base reference, an 8 bit time identifier and an 8 bit area identifier. These fields enable a decoder to selectively filter program guide data based on area and time based partitions.

In the VLPG data structure of Figure 1, a Master Database Table (MDBT item 122) is used to define program guide partitions (cells) and to inform a decoder of the cells available in its location for decoding. Figure 9 shows a Master Database Table data structure incorporating hierarchical based version identifiers
25 and cell partition identifiers advantageously enabling dynamic program guide re-partitioning. The code between items 170 and 178 comprises a loop that defines partitioned cells. Within this loop, the field called "cell_type" (item 172) determines an index of a cell as illustrated in Figure 10.

Figure 10 item 179 shows an exemplary data structure for a cell type indicator. The cell type indicator includes an 8 bit complexity level identifier used to define a complexity level of an object. The cell type indicator also includes an 8 bit area identifier and an 8 bit time identifier for defining area and time based
30
40 partitions.

12

5 An individual object or program guide information item includes a carouselId (as defined in Figure 8 and as shown item 150 in Figure 4) for linking the object to a time and area index of its mother cell. Dynamic program guide re-partitioning is achieved by re-arranging the cell list in the MDBT and by dynamic
10 alteration in the mother cell time and area index identifiers within a carouselId. Consequently, a guide provider is able to dynamically re-partition a program guide data structure to adapt to changes in available transmission bandwidth or decoder sophistication. A guide provider may use finer partitions to
15 provide faster object filtering times if increased bandwidth becomes available or may use coarser partitions to preserve bandwidth if decoder processing capabilities improve. As such, a decoder in San Diego may today have access to program guide information associated with areas 0 and 7 while in the future the
20 decoder may be given access to program guide information associated with areas 0 and 9, reflecting finer partitioning, for example. In the future, it is entirely feasible to be able to provide real-time access to multimedia objects present in guides covering areas as large as the USA by selecting an appropriate compromise
25 between bandwidth and partitioning.

Figure 11 shows a hierarchical directory format for an object database including object files under channel, event and control sub-directories. Figure 11 shows that a particular event such as "event2" can have its own directory containing its
30 required files, e.g., "event2" has four associated objects (items 240, 242, 244 and 246 in Figure 11). Using the object database a directory-based address is mapped into transport-level fields for processing. Given a path such as /VLPG/TIME1/AREA1/events/event2/event.bif, (path through
35 directory items 220, 224, 228, 232, 238, 242 of Figure 11) for example, there is one and only one object with a certain carouselId and moduleId. For example, in this case, the following mapping applies:

40 /VLPG -----> Files extracted from VLPG object data base

13

5 /TIME1 -----> 0x01 (time variable)
 /AREA1 -----> 0x01 (area variable)
 /events/event2 ---> 0x3005 (directory number variable).

Therefore, this database address is mapped to a
10 carouselId of 0x01013005. Further, the event.bif (item 242) has a
moduleId which may be determined from the program guide
information (such as value 0x0002 in this example). The inverse
mapping from transport-level fields to a directory-based address
is also unique and may be similarly derived.

15 The directory structure exemplified in Figure 11
supports the operation of software for processing and interacting
with transmitted objects. The processing software may be
transmitted in file form, together with objects, and then
interpreted or compiled and run by a decoder. Such processing
20 software may be used for numerous applications including for
advantageously creating content-based program guides in a
decoder in a language such as HTML (Hyper Text Mark-up
Language), SGML (Standardized Generalized Mark-up Language),
Java, ActiveX and any other decoder supported language. As an
25 example, each Sunday a guide provider may want to prepare a
web site describing all available Sunday movies for transmission
to decoder units containing a web browser and supporting HTML
software. The Sunday guide information is encoded in HTML and
transmitted to decoders as HTML software files that describe the
30 special web site. The HTML files are located anywhere in the
directory structure of the Object Database and together generate
images, text, video, and audio files that form the Sunday movie
guide listing comprising the special web site. As such, the Sunday
guide web site is broadcast as part of an object database and is not
35 conventionally accessed from an Internet server. Other special
program guide web sites that may be conveyed in this way may
list, for example, (a) a DVD/VCR programs available for play, (b)
other Internet web sites, (c) pre-stored fax/phone numbers for
access, (d) videophone functions and (e) home appliance control
40 functions.

- 5 A User may initiate display of the special Sunday
guide broadcast-web site contained in the Object Database by
using a remote unit or other data entry device to select an
associated displayed menu item or display icon and may similarly
navigate the broadcast-web site and review the advertised
10 movies. In addition, a User may be able to initiate commands via
the web site such as (a) programming a VCR or DVD unit, (b)
tuning to a desired channel, or (c) accessing other Internet sites
that are either similarly broadcast as part of the object database
or that are conventionally accessed via telephone (or cable) line.
15 Further, in initiating such telephone (or cable) line Internet access
a decoder may acquire access information from a broadcast or
other source. Such access information includes (a) an Internet URL,
(b) an Internet IP address, (c) an Email address, and (d) a
telephone/fax/videophone number, for example.
- 20 The hierarchical directory structure of Figure 11
illustrates another advantage offered by the VLPG structure of
Figure 1. In a large program guide, managing the update of
constituent tables and objects involves examining a large quantity
of version numbers (thousands of version numbers may be
25 involved). A decoder downloads a particular program guide table
or object upon determination of a version number change and
disregards those tables or objects where no version number
change is indicated. This task may be aided by listing all the
version numbers of tables and objects that are susceptible to
30 change in one table such as a MGT. The MGT is broadcast at a
sufficiently fast rate to enable a decoder to examine the MGT to
determine which tables or objects have changed and to acquire a
changed table or object in a timely fashion. However, parsing
every entry in the MGT may become very time consuming in a
35 large guide structure.

This problem is addressed by employing a system of
hierarchical version control in which there are several tables that
perform version control. These tables are arranged in a tree
structure as exemplified by Figure 11. In Figure 11, table 238
40 (event2) controls the version of those tables/files under table 238.

15

- 5 Table 232 (events) controls all the versions of tables 336 (event1), and 238. Table 228 (AREAl) controls the versions of tables 230 (channels), 232 and 236 (control) only. In this way, the version number information stored in each table is small and by traversing the tree from top to down, it is possible to quickly find
10 those files, tables or objects that need to be updated.

- Although a multiple-level structure is described above, a two layer version control structure may also be used for version control of objects in the database in the VLPG of Figure 1. In the two layer example, the upper layer of the tree hierarchy is the
15 Master Database Table (MDBT) as exemplified in Figure 9. The second level, below the MDBT level, consist of cells comprising Channel, Event and Control Basic Information Files, as exemplified by the previously described data structures of Figures 5, 6 and 7 respectively. A change in any of the Channel, Event or Control files
20 is signaled by a change in their respective version numbers, item 160 (Figure 5), item 163 (Figure 6) and item 167 (Figure 7). Further, any change in the Channel, Event or Control file version numbers is signaled by a change in the next hierarchical (cell) level version number i.e. such a change is signaled by a change in
25 version number 176 in the MDBT of Figure 9. As a specific example, if a channel logo (which is an image in the database) changes from one version to another, then the channel BIF will reflect this change in item 160 (Figure 5). The MDBT will also signal the change in item 176 at the cell level (Figure 9). A
30 decoder examines first the MDBT and determines the cell version number has changed and then examines the BIF files to identify objects that have changed within the cell.

- The Master Data Base Table (MDBT) structure of Figure 9 provides another advantage in processing large program guides.
35 Decoder sophistication and processing power and ability to process complex multimedia objects evolves with time. For example, the first generations of set top box decoders were largely restricted to processing images in bit map form. However, newer generations of decoder may use decompression software to download JPEG, GIF
40 or other image formats and future generations will be able to

The MDBT data structure of Figure 9 (and Figure 10) advantageously supports efficient multimedia object complexity discrimination in a decoder unit. For this purpose, the MDBT assigns PID (packet identifier) values to cells in the database. In Figure 9, item 172 identifies a particular cell and is associated with a PID value by item 174. Further, item 172 defines the 24-bit field cell_type that defines the time, area, and complexity coordinates of a cell (see Figure 10). As such, an object complexity level indicator is included in an MPEG-2 compatible transport-layer field. Thereby objects in the data base belonging to different complexity levels are conveyed in streams identified by different PIDs. A decoder is pre-assigned a complexity level and the decoder applies the MDBT (specifically item 172) in selecting and caching the PID values for those cells with complexity levels that match or are below the pre-assigned decoder complexity level. Objects of complexity level exceeding the decoders capabilities are advantageously discarded at the transport level.

Figure 12 shows a flowchart of a method for forming program specific information, according to the invention. The method of Figure 12 generates program specific information including MGT, MDBT, CCT, STT, RRT, TCIT, CCIT, SCIT and SIT data and descriptors containing the advantageous features previously described. The method may be employed at an encoder for broadcasting program guide data or, may be employed for encoding program guide data within a decoder unit for transmission to another device.

5 Following the start at step 250 of Figure 12, in step
253, a method based on the previously described data structuring
principles is selected for partitioning program specific information.
The program specific information is partitioned in accordance with
time segments and areas, network types, complexity levels, cells,
10 and programs (events). In step 255, PID values are assigned to
accommodate the partitioned program specific information. If a
non-MPEG transport protocol is used, PID values may be replaced
by proper parameters that identify logical channels. In step 257 a
MGT and MDBT (or other type of control tables) are generated to
15 include those formed during partition operations. The MGT
conveys information for use in acquiring program specific
information conveyed in other tables. The MDBT conveys
information for use in acquiring multimedia objects from a
transport stream.

20 In step 260 individual CCT, STT, RRT, TCIT, CCIT, SCIT
and SIT etc. tables are formed complying with the partitioned
structure. The individual tables incorporate multimedia object
links, version numbers and identifiers derived according to the
previously described invention principles. A CIT (e.g. TCIT, CCIT
25 and SCIT) is formed containing channel and program identification
information enabling acquisition of available broadcast programs
and channels containing packet identifiers for identifying
individual packetized datastreams that constitute individual
programs to be transmitted on particular channels. Further, in
30 step 260, an SIT is generated containing program guide schedule
information including descriptive lists of programs (events)
receivable on the channels listed in the CIT.

 In step 263, the tables formed in step 260, together
with associated multimedia objects, are formatted to be
35 compatible with a desired data format and protocol. Such data
formats and protocols include, for example, MPEG2 compatible
Program Specific Information, MPEG2 DSM-CC, DSS, and an
Internet compatible file transfer format. In step 265, the resulting
formatted tables and multimedia objects are incorporated into a
40 datastream in their designated locations for terrestrial

5 transmission. The MGT and MDBT are incorporated into the datastream in step 267.

In step 270, the program specific information produced in step 267, together with video and audio program representative components (and other data) for multiple channels,
10 is multiplexed and formatted into a transport stream for output. In step 270, the output transport stream is further processed to be suitable for terrestrial transmission to another device such as a receiver, video server, or storage device for recording on a storage medium, for example. The processes performed in step 270
15 include known encoding functions such as data compression Reed-Solomon encoding, interleaving, scrambling, trellis encoding, and carrier modulation. The process is complete and terminates at step 275. In the process of Figure 12, multiple CIT, SIT and associated extension tables may be formed and incorporated in the program
20 specific information in order to accommodate expanded numbers of channels. Further, in other embodiments the tables may be similarly processed for satellite, cable or Internet transmission, for example.

In the video receiver system of Figure 13, a broadcast
25 carrier modulated with signals carrying audio, video and associated data representing broadcast program content is received by antenna 10 and processed by unit 13. The resultant digital output signal is demodulated by demodulator 15. The demodulated output from unit 15 is trellis decoded, mapped into
30 byte length data segments, deinterleaved and Reed-Solomon error corrected by decoder 17. The corrected output data from unit 17 is in the form of an MPEG compatible transport datastream containing program representative multiplexed audio, video and data components. The transport stream from unit 17 is
35 demultiplexed into audio, video and data components by unit 22 which are further processed by the other elements of decoder system 100. In one mode, decoder 100 provides MPEG decoded data for display and audio reproduction on units 50 and 55 respectively. In another mode, the transport stream from unit 17
40 is processed by decoder 100 to provide an MPEG compatible

- 5 datastream for storage on storage medium 105 via storage device 90.

A user selects for viewing either a TV channel (user selected channel-SC) or an on-screen menu, such as a program guide, by using a remote control unit 70. Controller 60 uses the selection information provided from remote control unit 70 via interface 65 to appropriately configure the elements of Figure 13 to receive a desired program channel for viewing. Controller 60 comprises processor 62 and processor 64. Unit 62 processes (i.e. parses, collates and assembles) system timing information and program specific information including program guide information. Processor 64 performs the remaining control functions required in operating decoder 100. Although the functions of unit 60 may be implemented as separate elements 62 and 64 as depicted in Figure 13, they may alternatively be implemented within a single processor. For example, the functions of units 62 and 64 may be incorporated within the programmed instructions of a microprocessor.

Controller 60 configures processor 13, demodulator 15, decoder 17 and decoder system 100 to demodulate and decode the input signal format and coding type. Further, controller 60 configures units 13, 15, and 17 for other communication modes, such as for receiving cable television (CATV) signals and for bi-directional communication via coaxial line 14 or for bi-directional (e.g. Internet) communication, for example, via telephone line 11. In an analog video mode, an NTSC compatible signal is received by units 13, 15 and 17 and processed by decoder 100 for video display and audio reproduction on units 50 and 55 respectively. Units 13, 15, 17 and sub-units within decoder 100 are individually configured for the input signal type by controller 60 setting control register values within these elements using a bi-directional data and control signal bus C.

The transport stream provided to decoder 100 comprises data packets containing program channel data and ancillary system timing information and program specific information including program guide information. Unit 22 directs

20

- 5 the ancillary information packets to controller 60 which parses, collates and assembles this information into the previously described hierarchically arranged tables (as exemplified in Figure 1). Individual data packets comprising the User selected program channel SC are identified and assembled using the assembled
10 program specific information. Further, the program specific information contains conditional access, network information and identification and linking data enabling the system of Figure 13 to tune to a desired channel and assemble data packets to form complete programs. The program specific information also
15 contains data supporting the identification and assembly of the ancillary information.

- The program specific and system timing information is assembled by controller 60 into multiple hierarchically arranged and inter-linked tables per the structure of Figure 1. The STT
20 contains a time reference indicator and associated correction data sufficient for a decoder to establish a time of transmission of a program by a broadcast source. The MGT contains information for acquiring program specific information conveyed in other tables such as identifiers for identifying data packets associated with the
25 other tables. The CIT (e.g. TCIT) contains information for tuning and navigation to receive a User selected program channel. The SIT contains descriptive lists of programs (events) receivable on the channels listed in the CIT. The RRT contains program content rating information such as the MPAA (Motion Picture Association
30 of America) or V-chip compatible rating information that is collated by region (e.g. by country or by state within the USA). Additional program specific information describing and supplementing items within the hierarchical tables is conveyed within descriptor information elements. The program specific and
35 system timing information acquired by controller 60 via unit 22 is stored within internal memory of unit 60. Controller 60 uses the acquired program guide information in conditioning access to programs and in scheduling program processing functions including program viewing, recording and playback.

5 Controller 60 and processor 22 determine from the CIT the PIDs of video, audio and sub-picture streams in the packetized decoded transport stream input to decoder 100 from unit 17. The video, audio and sub-picture streams constitute the desired program being transmitted on selected channel SC. Processor 22
10 provides MPEG compatible video, audio and sub-picture streams to video decoder 25, audio decoder 35 and sub-picture processor 30 respectively. The video and audio streams contain compressed video and audio data representing the selected channel SC program content. The sub-picture data contains the SIT, CCT and
15 RRT information associated with the channel SC program content.

Decoder 25 decodes and decompresses the MPEG compatible packetized video data from unit 22 and provides decompressed program representative pixel data to NTSC encoder 45 via multiplexer 40. Similarly, audio processor 35 decodes the
20 packetized audio data from unit 22 and provides decoded and amplified audio data, synchronized with the associated decompressed video data, to device 55 for audio reproduction. Processor 30 decodes and decompresses sub-picture data received from unit 22.

25 Processor 30 assembles, collates and interprets RRT, CCT, CIT and data objects from unit 22 to produce formatted program guide data for output to OSD 37. OSD 37 processes the SIT, RRT, and CCT and other information to generate pixel mapped data representing subtitling, control and information menu
30 displays including selectable menu options and other items for presentation on the display device 50. The control and information menus that are displayed enable a user to select a program to view and to schedule future program processing functions including a) tuning to receive a selected program for viewing, b)
35 recording of a program onto storage medium 105, and c) playback of a program from medium 105.

The control and information displays, including text and graphics produced by OSD generator 37, are generated in the form of overlay pixel map data under direction of controller 60.
40 The overlay pixel map data from unit 37 is combined and

22

5 synchronized with the decompressed pixel representative data from MPEG decoder 25 in encoder 45 via multiplexer 40 under direction of controller 60. Combined pixel map data representing a video program on channel SC together with associated sub-picture data is encoded by NTSC encoder 45 and output to device 50 for
10 display.

In a storage mode of the system of Figure 13, the corrected output data from unit 17 is processed by decoder 100 to provide an MPEG compatible datastream for storage. In this mode, a program is selected for storage by a user via remote unit 70 and
15 interface 65. Processor 22, in conjunction with processor 60 forms condensed program specific information including MGT, MDBT, CCT, STT, RRT, TCIT and SIT data and descriptors containing the advantageous features previously described. The condensed program specific information supports decoding of the program
20 selected for storage but excludes unrelated information. Processor 60, in conjunction with processor 22 forms a composite MPEG compatible datastream containing packetized content data of the selected program and associated condensed program specific information. The composite datastream is output to storage
25 interface 95.

Storage interface 95 buffers the composite datastream to reduce gaps and bit rate variation in the data. The resultant buffered data is processed by storage device 90 to be suitable for storage on medium 105. Storage device 90 encodes the buffered
30 datastream from interface 95 using known error encoding techniques such as channel coding, interleaving and Reed Solomon encoding to produce an encoded datastream suitable for storage. Unit 90 stores the resultant encoded datastream incorporating the condensed program specific information on medium 105.

35 The architecture of Figure 13 is not exclusive. Other architectures may be derived in accordance with the principles of the invention to accomplish the same objectives. Further, the functions of the elements of decoder 100 of Figure 13 and the process steps of Figure 12 may be implemented in whole or in
40 part within the programmed instructions of a microprocessor. In

5 addition, the principles of the invention apply to any form of MPEG or non-MPEG compatible electronic program guide. A datastream formed according to the invention principles may be used in a variety of applications including video server or PC type communication via telephone lines, for example. A program
10 datastream with one or more components of video, audio and data formed to incorporate program specific information according to invention principles may be recorded on a storage medium and transmitted or re-broadcast to other servers, PCs or receivers. The key elements of the data structure described herein may be
15 advantageously used for conveying program ancillary information in a wide variety of data transport structures that may be used to deliver program content or program guide information. Such transport structures, for example, may include MPEG-PSI, Internet TCP/IP (Transport Control Protocol/Internet Protocol), DSS (Digital
20 Satellite System), ATM (Asynchronous Transfer Mode) etc.

RCA 88914

M 21.02.00

24

CLAIMS

1. Apparatus for decoding packetized program information from a first source to provide a program guide, comprising:

a processor for acquiring ancillary and program guide information in said packetized program information, said ancillary information including,

(a) channel mapping information enabling a user of said decoding apparatus to select between different groups of broadcast services collated by area, and

(b) data for collating program guide information associated with said broadcast services by scheduled time of broadcast, and

a data collator for collating said program guide information associated with said broadcast services using said ancillary information; and

a display processor for processing said collated program guide information for display.

2. Apparatus according to claim 1, wherein

said area comprises at least one of (a) a geographic area, (b) an area served by a satellite, terrestrial, or cable broadcaster, and (c) a market area of a service provider.

3. Apparatus according to claim 1, wherein

said channel mapping information comprises at least one of (a) a channel information map associating particular broadcast channels with particular areas, and (b) a service information map associating particular services with particular areas.

4. Apparatus according to claim 3, wherein said services comprise at least two of

(a) video channels, (b) audio channels, (c) Internet service, (d) phone or fax service, (e) Wide Area Network service.

5. Apparatus according to claim 1, wherein

said channel mapping information associates particular broadcast channels with a region identification designation.

AMENDED SHEET

RCA 88914

N 21.02.00

25

6. Apparatus according to claim 5, wherein

said region identification designation comprises at least one of (a) a zip code, (b) a telephone area code, and (c) another region identification code, and

said data collator collates program guide information by comparing said region identification designation with a pre-stored region identification designation of said apparatus.

7. Apparatus according to claim 1, wherein

said ancillary information includes objects associated with said program guide information and includes information partitioned into tables, and

said processor acquires data for collating said tables and objects by area.

8. Apparatus according to claim 7, wherein

said data for collating said tables and objects includes region identification designations for associating objects with regions that are different to table regions, and

said data collator collates said objects into regions different to regions of said tables.

9. Apparatus according to claim 7, wherein

said object comprises at least one of (a) a video segment, (b) an audio segment, (c) text, (d) an icon representing a user selectable item for display, (e) an HTML or SGML document (f) a menu of selectable items, (g) an image window for presentation within an encompassing image, and (h) an image window for initiating a multimedia function.

10. Apparatus according to claim 1, wherein

said ancillary information further includes acquisition information for use in acquiring said ancillary information from a second source different to said first source, and

said acquisition information includes one of (a) an Internet URL, (b) an Internet IP address, (c) an Email address, and (d) a telephone/fax/videophone number.

AMENDED SHEET

RCA 88914

71.21.02.00

26

11. Apparatus according to claim 1, wherein
said channel mapping information is formed in accordance with MPEG
protocol and uses at least one data field selected from, (a) a table_id_extension field, (b)
a carousel field, and (c) a User defined private data field.

12. Apparatus according to claim 1, wherein
said data collator collates said program guide information in response to a
User selection input to provide a program guide selected from at least two available
program guides associated with different areas.

13. Apparatus according to claim 1, wherein
said ancillary information is partitioned by area at the transport protocol
level enabling filtering of said ancillary information by area prior to post-transport
processing.

14. Apparatus according to claim 1, wherein
said ancillary information is partitioned by area enabling different ancillary
information elements to be targeted for decoding in corresponding different areas.

15. Apparatus for decoding packetized program information from a first
source to provide a program guide, comprising:

a processor for acquiring ancillary and program guide information in said
packetized program information, said ancillary information including,

(a) channel mapping information enabling a user of said decoding
apparatus to select between different groups of broadcast services collated by area, and

(b) data for collating program guide information associated with
said broadcast services by scheduled time of broadcast, and

a data collator for collating program guide information in response to a
User selection input to provide a program guide selected from at least two available
program guides associated with different areas; and

a display processor for processing said collated program guide
information for display.

AMENDED SHEET

RCA 88914

14.02.00

27

16. A storage medium containing digital data representing video information comprising:

packetized program information representing a video program; and
ancillary information including ancillary and program guide information in said packetized program information, said ancillary information including,

(a) channel mapping information suitable for enabling a user of a reproduction device for playing said digital data to be able select between different groups of broadcast services and associated tables and objects collated by area, and

(b) data for collating program guide information associated with said broadcast services, and

information for associating said tables and objects with program guide information items associated with said broadcast services.

17. Apparatus according to claim 16, wherein

said channel mapping information includes a program information map linking said objects with program guide information items associated with programs broadcast on particular broadcast channels.

18. A method for forming program guide information to be suitable for processing in a decoder to provide different program guides displaying different service listings in correspondingly different regions, comprising the steps of:

forming ancillary information including,

(a) channel mapping information enabling a user of said decoding apparatus to select between different groups of broadcast services collated by area, and

(b) data for collating program guide information associated with said broadcast services by scheduled time of broadcast, and

forming linking information associating programs with said broadcast services; and

incorporating said ancillary information and said linking information into packetized data for output to a transmission channel.

19. A method according to claim 18, wherein

said area comprises at least one of (a) a geographic area, (b) an area served by a satellite, terrestrial, or cable broadcaster, and (c) a market area of a service provider.

AMENDED SHEET

RCA 88914

M 21.02.00

28

20. A method according to claim 18, wherein
said channel mapping information comprises at least one of (a) a channel
information map associating particular broadcast channels with particular areas, and (b)
a service information map associating particular services with particular areas.

21. A method according to claim 18, wherein
said channel mapping information associates particular broadcast
channels with a region identification designation.

22. A method according to claim 21, wherein
said region identification designation comprises at least one of (a) a zip
code, (b) a telephone area code, and (c) another region identification code.

23. A method according to claim 18, including the step of
forming said ancillary information into tables partitioned based on area
and scheduled broadcast time.

24. A method according to claim 18, wherein
said ancillary information includes an object associated with said program
guide information.

25. A method according to claim 24, wherein
said object comprises at least one of (a) a video segment, (b) an audio
segment, (c) text, (d) an icon representing a user selectable item for display, (e) an
HTML or SGML document (f) a menu of selectable items, (g) an image window for
presentation within an encompassing image, and (h) an image window for initiating a
multimedia function.

26. A method according to claim 18, including the step of
forming ancillary information partitioned into tables and including data for
collating objects and said tables, and
including region identification designations for associating objects with
regions that are different to table regions.

AMENDED SHEET

RCA 88914

H 21.02.00

29

27. A method according to claim 18, including the step of forming said ancillary information to include information associating a particular area with at least one particular decoder for decoding said ancillary information.

28. A method according to claim 27, wherein said particular decoder is associated with said particular area using a unique decoder identification code.

29. A method according to claim 27, including the step of dynamically updating said information associating a particular area with at least one particular decoder to associate a different area with said particular decoder.

30. A method according to claim 18, wherein said channel mapping information is formed in accordance with MPEG protocol and uses at least one data field selected from, (a) a table_id_extension field, (b) a carousel_id field, and (c) a User defined private data field.

31. A method for decoding packetized program information from a first source to provide a program guide, comprising the steps of:

acquiring ancillary and program guide information in said packetized program information, said ancillary information including,

(a) channel mapping information enabling a user of said decoding apparatus to select between different groups of broadcast services collated by area, and

(b) data for collating program guide information associated with said broadcast services by scheduled time of broadcast, and

collating said program guide information associated with said broadcast services using said ancillary information; and

processing said collated program guide information for display.

AMENDED SHEET

RCA 88914

M 21:02:00

30

32. A method for decoding packetized program information from a first source to provide a program guide, comprising the steps of:

acquiring ancillary and program guide information in said packetized program information, said ancillary information including,

(a) channel mapping information enabling a user of said decoding apparatus to select between different groups of broadcast services collated by area, and

(b) data for collating program guide information associated with said broadcast services by scheduled time of broadcast, and

collating program guide information in response to a User selection input to provide a program guide selected from at least two available program guides associated with different areas; and

processing said collated program guide information for display.

AMENDED SHEET

ABSTRACT

A program guide information data structure and processing system for processing large quantities of guide information facilitates achieving a desirable compromise between transmission bandwidth and decoder complexity. A decoder acquires data for collating program guide information including objects by both area (e.g. a geographic, broadcast, or network market area), and by scheduled time of broadcast. The decoder collates the program guide information using the collation data which comprises channel and program map information for associating the program guide information with particular areas and broadcast times. The decoder collates the program guide information to provide a program guide selected from at least two available program guides associated with different areas in response to a User selection input. The collated program guide information is processed for display.

1/11




FIG. 1

2/11

130

SYNTAX	BITS	FORMAT
master_guide_table_section () {		
table_id	8	0x91
section_syntax_indicator	1	'1'
private_indicator	1	'1'
reserved	2	'11'
section_length	12	uimbsf
network_provider	16	uimbsf
reserved	2	'11'
version_number	5	uimbsf
current_next_indicator	1	'1'
section_number	8	0x00
last_section_number	8	0x00
protocol_version	8	uimbsf
number_networks_defined	16	uimbsf
table_types_defined	16	uimbsf
for (i=0; i<table_types_defined; i++){		
table_type	16	uimbsf
reserved	3	'111'
table_type_PID	13	uimbsf
reserved	3	'111'
table_type_version_number	5	uimbsf
number_bytes	32	uimbsf
reserved	4	'1111'
table_type_descriptors_length	12	uimbsf
for (k=0; k<N; k++){		
descriptor()	var	
}		
reserved	4	'1111'
descriptors_length	12	uimbsf
for (l = 0; l<N; l++){		
descriptor()	var	
CRC_32	32	rpchof
}		

FIG. 2

3/11

140

SYNTAX	BITS	FORMAT
terrestrial_channel_information_table_section () {		
table_id	8	0x95
section_syntax_indicator	1	'1'
private_indicator	1	'1'
reserved	2	'11'
section_length	12	uimsbf
network_provider	16	uimsbf
reserved	2	'11'
version_number	5	uimsbf
current_next_indicator	1	bslbf
section_number	8	uimsbf
last_section_number	8	uimsbf
protocol_version	8	uimsbf
num_channels_in_section	8	uimsbf
for (i=0;i<num_channels_in_section;i++){		
short name	7*16	unicode BMP
reserved	4	'1111'
major_channel_number	10	uimsbf
minor_channel_number	10	uimsbf
modulation_mode	8	uimsbf
carrier_frequency	32	uimsbf
channel_TSID	16	uimsbf
program_number	16	uimsbf
access_controlled	1	bslbf
hidden	1	bslbf
reserved	8	0xFF
service_type	6	uimsbf
source_id	16	uimsbf
carousel_id	32	uimsbf
reserved	6	'111111'
descriptors_length	10	uimsbf
for (i=0;i<N _i ;i++){		
descriptors()		
}		
} reserved	6	'111111'
additional_descriptors_length	10	uimsbf
for(j=0;j<N _j ;j++){		
additional_descriptors()		
}		
CRC_32	32	rpchof
}		

FIG. 3

4/11

SYNTAX	BITS	FORMAT
multimedia_object_section () {		
table_id	8	0x3C
section_syntax_indicator	1	'1'
private_indicator	1	'1'
reserved	2	'11'
section_length	12	uimsbf
moduleId	16	uimsbf
reserved	2	'11'
version_number	5	uimsbf
current_next_indicator	1	'1'
section_number	8	uimsbf
last_section_number	8	uimsbf
protocolDiscriminator	8	0x11
dsmccType	8	0x03
messageId	16	0x1003
carouselId	32	uimsbf
reserved	8	0xFF
adaptionLength	8	0x00
messageLength	16	uimsbf
moduleId	16	uimsbf
moduleVersion	8	uimsbf
reserved	8	0xFF
blockNumber	16	uimsbf
Object_data ()	32	rpchof
CRC_32		
}		

150

FIG. 4

5/11

SYNTAX	BITS	FORMAT
channel_basic_information_file_section () {		
table_id	8	0x3C
section_syntax_indicator	1	'1'
private_indicator	1	'1'
reserved	2	'11'
section_length	12	uimbsf
moduleId	16	0x0001
reserved	2	'11'
version_number	5	uimbsf
current_next_indicator	1	'1'
section_number	8	0x00
last_section_number	8	0x00
protocolDiscriminator	8	0x11
dsmccType	8	0x03
messageId	16	0x1003
carouselId	32	uimbsf
reserved	8	0xFF
adaptionLength	8	0x00
messageLength	16	uimbsf
moduleId	16	0x0001
moduleVersion	8	uimbsf
reserved	8	0xFF
blockNumber	16	0x0000
number_modules	16	uimbsf
for (i=0;i<number_modules;i++){		
moduleId	16	uimbsf
number_blocks	16	uimbsf
reserved	4	'1111'
moduleSize	28	uimbsf
moduleVersion	8	uimbsf
}		
reserved	4	'1111'
descriptors_length	12	
for (i=0;i<N;i++) {		
descriptor()		
}		
CRC_32	32	rpchof
}		

FIG. 5

6/11

SYNTAX	BITS	FORMAT
event_basic_information_file_section () {		
table_id	8	0x3C
section_syntax_indicator	1	'1'
private_indicator	1	'1'
reserved	2	'11'
section_length	12	uimbsf
moduleId	16	0x0002
reserved	2	'11'
version_number	5	uimbsf
current_next_indicator	1	'1'
section_number	8	0x00
last_section_number	8	0x00
protocolDiscriminator	8	0x11
dsmccType	8	0x03
messageId	16	0x1003
carouselId	32	uimbsf
reserved	8	0xFF
adaptionLength	8	0x00
messageLength	16	uimbsf
moduleId	16	0x0002
moduleVersion	8	uimbsf
reserved	8	0xFF
blockNumber	16	0x0000
title_length	8	uimbsf
title_text()	var	
number_modules	16	uimbsf
for (i=0;i<number_modules;i++) {		
moduleId	16	uimbsf
number_blocks	16	uimbsf
reserved	4	'1111'
moduleSize	28	uimbsf
moduleVersion	8	uimbsf
}		
reserved	4	'1111'
descriptors_length	12	
for (i=0;i<N;i++) {		
descriptor()		
}		
CRC_32	32	rpchof
}		

FIG. 6

7/11

SYNTAX	BITS	FORMAT
control_basic_information_file_section () {		
table_id	8	0x3C
section_syntax_indicator	1	'1'
private_indicator	1	'1'
reserved	2	'11'
section_length	12	uimsbf
moduleId	16	0x0003
reserved	2	'11'
version_number	5	uimsbf
current_next_indicator	1	'1'
section_number	8	0x0000
last_section_number	8	0x0000
protocolDiscriminator	8	0x11
dsmccType	8	0x03
messageId	16	0x1003
carouselId	32	uimsbf
reserved	8	0xFF
adaptionLength	8	0x00
messageLength	16	uimsbf
moduleId	16	0x0003
moduleVersion	8	uimsbf
reserved	8	0xFF
blockNumber	16	0x0000
number_modules	16	uimsbf
for (i=0;i<number_modules;i++) {		
moduleId	16	uimsbf
number_blocks	16	uimsbf
reserved	4	'1111'
moduleSize	28	uimsbf
moduleVersion	8	uimsbf
}		
reserved	4	'1111'
descriptors_length	12	
for (i=0;i<N;i++) {		
descriptor()		
}		
CRC_32	32	rpchof
}		

FIG. 7

	MSB				LSB	
Bit	31	24	23	16	15	0
carouselId	time		area		dirNumber	

FIG. 8

SYNTAX	BITS	FORMAT
master_database_table_section () {		
table_id	8	0x92
section_syntax_indicator	1	'1'
private_indicator	1	'1'
reserved	2	'11'
section_length	12	uimsbf
table_id_extension	16	0x0000
reserved	2	'11'
version_number	5	uimsbf
current_next_indicator	1	'1'
section_number	8	uimsbf
last_section_number	8	uimsbf
protocol_version	8	uimsbf
number_cells_defined	24	uimsbf
number_cells_in_section	24	uimsbf
for (i=0;i<number_cells_in_section;i++) {		
cell_type	24	uimsbf
reserved	3	'111'
cell_type_PID	13	uimsbf
reserved	3	'111'
cell_type_version_number	5	uimsbf
number_bytes	32	uimsbf
reserved	4	'1111'
cell_type_descriptors_length	12	uimsbf
for (k=0;k<N;k++)		
descriptor()	var	
}		
CRC_32	32	rpchof
}		

FIG. 9

	MSB				LSB		
Bit	23	16	15	8	7	0	
cell_type	time				complexity		

FIG. 10




FIG. 11





FIG. 12

FIG. 13



As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

A MULTIMEDIA SYSTEM FOR ADAPTIVELY FORMING AND PROCESSING

EXPANSIVE PROGRAM GUIDES

the specification of which (check only one item below):

☐ is attached hereto.

☐ was filed as United States application

Serial No. _____

on _____

and was amended

on _____ (if applicable).

☒ was filed as PCT international application

Number PCT/US99/03513

on 18 February 1999

and was amended under PCT Article ~~33~~ 34

on 18 February 2000 (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

PRIOR FOREIGN/PCT APPLICATION(S) AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. 119:

COUNTRY (if PCT, indicate "PCT")	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 USC 119
			<input type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO

Rec'd POT/PTO 19 MAR 2001

I hereby claim the benefit under Title 35, United States Code, §120 of one or more prior application(s) in the national or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:

U.S. APPLICATIONS

STATUS (Check one)

U.S. APPLICATION NUMBER

U.S. FILING DATE

PATENTED

PENDING

ABANDONED

60/075,412

20 February 1998

PCT APPLICATIONS DESIGNATING THE U.S.

PCT APPLICATION NO.

PCT FILING DATE

U.S. SERIAL NUMBERS
ASSIGNED (if any)

PCT/US99/03513

18 February 1999 (18.02.99)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (List name and registration number)

Joseph S. Tripoli

- Reg. No. 26,040

Eric P. Herrmann

- Reg. No. 29,169

Alexander J. Burke

- Reg. No. 40,425

Send Correspondence to:

Joseph S. Tripoli - Patent Operations

THOMSON multimedia Licensing Inc.

PO Box 5312

Princeton, New Jersey 08540 US

Direct Telephone Calls to:
(name and telephone number)

609-734-9503

FULL NAME OF INVENTOR OZKAN	FAMILY NAME OZKAN	FIRST GIVEN NAME Mehmet	SECOND GIVEN NAME Kemal
CITY Istanbul	STATE OR FOREIGN COUNTRY Turkey	COUNTRY OF CITIZENSHIP TR	
POST OFFICE ADDRESS Maltepe Mah. Aydin Sok. 82222091 Apt. 10/11	CITY Istanbul	STATE & ZIP CODE/COUNTRY Maltepe 81580/TR	
FULL NAME OF INVENTOR TENG	FAMILY NAME TENG	FIRST GIVEN NAME Chia-Yuan	SECOND GIVEN NAME
CITY San Diego	STATE OR FOREIGN COUNTRY California	COUNTRY OF CITIZENSHIP Taiwan	
POST OFFICE ADDRESS 7384 Celata Lane	CITY San Diego	STATE & ZIP CODE/COUNTRY California 92129/US	
FULL NAME OF INVENTOR HEREDIA	FAMILY NAME HEREDIA	FIRST GIVEN NAME Edwin	SECOND GIVEN NAME Arturo
CITY San Jose	STATE OR FOREIGN COUNTRY California	COUNTRY OF CITIZENSHIP Boliva	
POST OFFICE ADDRESS 1700 North First Street #235	CITY San Jose	STATE & ZIP CODE/COUNTRY California 95112/US	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

SIGNATURE OF INVENTOR 01 Mehmet Kemal Ozkan	SIGNATURE OF INVENTOR 02 Chia-Yuan Teng	SIGNATURE OF INVENTOR 03 Edwin Arturo Heredia
DATE 23 January 2001	DATE 2000	DATE Aug. 7, 2000

Continued Declaration for Patent Application and Power of Attorney

(Includes Reference to PCT International Applications)

ATTORNEY'S DOCKET NUMBER

RCA 88914

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

A MULTIMEDIA SYSTEM FOR ADAPTIVELY FORMING AND PROCESSING

EXPANSIVE PROGRAM GUIDES

the specification of which (check only one item below):

☐ is attached hereto.

☐ was filed as United States application

Serial No. _____

on _____,

and was amended

on _____ (if applicable).

☒ was filed as PCT international application

Number PCT/US99/03513

on 18 February 1999,

and was amended under PCT Article ~~32~~ 34

on 18 February 2000 (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

PRIOR FOREIGN/PCT APPLICATION(S) AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. 119:

COUNTRY (if PCT, indicate "PCT")	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 USC 119
			<input type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO

Combined Declaration For Patent Application and Power of Attorney (Continued)

(Includes Reference to PCT International Applications)

ATTORNEY'S DOCKET NUMBER
RCA 88914

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:

U S APPLICATIONS		STATUS (Check one)		
U S APPLICATION NUMBER	U S FILING DATE	PATENTED	PENDING	ABANDONEED
60/075,412	20 February 1998			
PCT APPLICATIONS DESIGNATING THE U S				
PCT APPLICATION NO	PCT FILING DATE	U S SERIAL NUMBERS ASSIGNED (if any)		
PCT/US99/03513	18 February 1999 (18.02.99)			

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (List name and registration number)

Joseph S. Tripoli - Reg. No. 26,040
Eric P. Herrmann - Reg. No. 29,169
Alexander J. Burke - Reg. No. 40,425

Send Correspondence to:

Joseph S. Tripoli - Patent Operations
THOMSON multimedia Licensing Inc.
PO Box 5312
Princeton, New Jersey 08540 US

Direct Telephone Calls to: (name and telephone number)

609-734-9503

201	FULL NAME OF INVENTOR	FAMILY NAME	OZKAN	FIRST GIVEN NAME	Mehmet	SECOND GIVEN NAME	Kemal
	RESIDENCE & CITIZENSHIP	CITY	Istanbul	STATE OR FOREIGN COUNTRY	Turkey	COUNTRY OF CITIZENSHIP	TR
	POST OFFICE ADDRESS	Idealtepe Mah. Aydin Sok. Sec. 209/11 Apt. 10/11					
202	FULL NAME OF INVENTOR	FAMILY NAME	TENG	FIRST GIVEN NAME	Chia-Yuan	SECOND GIVEN NAME	
	RESIDENCE & CITIZENSHIP	CITY	San Diego CA	STATE OR FOREIGN COUNTRY	California	COUNTRY OF CITIZENSHIP	Taiwan
	POST OFFICE ADDRESS	7384 Celata Lane					
203	FULL NAME OF INVENTOR	FAMILY NAME	HEREDIA	FIRST GIVEN NAME	Edwin	SECOND GIVEN NAME	Arturo
	RESIDENCE & CITIZENSHIP	CITY	San Jose	STATE OR FOREIGN COUNTRY	California	COUNTRY OF CITIZENSHIP	Bolivia
	POST OFFICE ADDRESS	1700 North First Street #235					

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

SIGNATURE OF INVENTOR 201	SIGNATURE OF INVENTOR 202	SIGNATURE OF INVENTOR 203
Mehmet Kemal Ozkan	Chia-Yuan Teng	Edwin Arturo Heredia
DATE	DATE	DATE
2000	Aug 16 2000	2000